

**IMT cellular networks;  
Harmonised Standard covering the essential  
requirements of article 3.2 of the Directive 2014/53/EU;  
Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA)  
User Equipment (UE)**  
(ETSI EN 301 908-13 V11.1.1 (2016-07))

Copyright OVE

---

**Medieninhaber und Hersteller:**  
OVE Österreichischer Verband für Elektrotechnik  
Austrian Standards Institute

**ICS** 33.070.01

**Copyright © OVE/Austrian Standards Institute – 2016.**  
**Alle Rechte vorbehalten!** Nachdruck oder  
Vervielfältigung, Aufnahme auf oder in sonstige Medien  
oder Datenträger nur mit Zustimmung gestattet!

**Ident (IDT) mit** ETSI EN 301 908-13 V11.1.1 (2016-07)

**Ersatz für** siehe nationales Vorwort

**Verkauf von in- und ausländischen Normen und  
technischen Regelwerken durch**  
Austrian Standards Institute  
Heinestraße 38, 1020 Wien  
E-Mail: sales@austrian-standards.at  
Internet: www.austrian-standards.at  
Webshop: www.austrian-standards.at/webshop  
Tel.: +43 1 213 00-300  
Fax: +43 1 213 00-818

**zuständig** OVE/Komitee  
TK IT-EG  
Informationstechnologie, Telekommunikation und  
Elektronik

Alle Regelwerke für die Elektrotechnik auch erhältlich bei  
OVE Österreichischer Verband für Elektrotechnik  
Eschenbachgasse 9, 1010 Wien  
E-Mail: verkauf@ove.at  
Internet: www.ove.at  
Webshop: www.ove.at/webshop  
Tel.: +43 1 587 63 73  
Fax: +43 1 587 63 73 - 99

## Nationales Vorwort

Diese Europäische Norm EN 301 908-13 V11.1.1:2016 hat sowohl den Status von ÖSTERREICHISCHEN BESTIMMUNGEN FÜR DIE ELEKTROTECHNIK gemäß ETG 1992 als auch den einer ÖNORM gemäß NG 1971. Bei ihrer Anwendung ist dieses Nationale Vorwort zu berücksichtigen.

Für den Fall einer undatierten normativen Verweisung (Verweisung auf einen Standard ohne Angabe des Ausgabedatums und ohne Hinweis auf eine Abschnittsnummer, eine Tabelle, ein Bild usw.) bezieht sich die Verweisung auf die jeweils neueste Ausgabe dieses Standards.

Für den Fall einer datierten normativen Verweisung bezieht sich die Verweisung immer auf die in Bezug genommene Ausgabe des Standards.

Der Rechtsstatus dieser ÖSTERREICHISCHEN BESTIMMUNGEN FÜR DIE ELEKTROTECHNIK/ÖNORM ist den jeweils geltenden Verordnungen zum Elektrotechnikgesetz zu entnehmen.

Bei mittels Verordnungen zum Elektrotechnikgesetz verbindlich erklärten ÖSTERREICHISCHEN BESTIMMUNGEN FÜR DIE ELEKTROTECHNIK/ÖNORMEN ist zu beachten:

- Hinweise auf Veröffentlichungen beziehen sich, sofern nicht anders angegeben, auf den Stand zum Zeitpunkt der Herausgabe dieser ÖSTERREICHISCHEN BESTIMMUNGEN FÜR DIE ELEKTROTECHNIK/ÖNORM. Zum Zeitpunkt der Anwendung dieser ÖSTERREICHISCHEN BESTIMMUNGEN FÜR DIE ELEKTROTECHNIK/ÖNORM ist der durch die Verordnungen zum Elektrotechnikgesetz oder gegebenenfalls auf andere Weise festgelegte aktuelle Stand zu berücksichtigen.
- informative Anhänge und Fußnoten sowie normative Verweise und Hinweise auf Fundstellen in anderen, nicht verbindlichen Texten werden von der Verbindlicherklärung nicht erfasst.

Europäische Normen (EN) werden durch Veröffentlichung eines identen Titels und Textes in das Gesamtwerk der ÖSTERREICHISCHEN BESTIMMUNGEN FÜR DIE ELEKTROTECHNIK/ÖNORMEN übernommen, wobei der Nummerierung der Zusatz ÖVE/ÖNORM bzw. ÖNORM vorangestellt wird.

Der von ETSI übermittelte Normentext wird in englischer Sprache veröffentlicht, da davon ausgegangen werden kann, dass die Anwender der Norm über ausreichende englische Sprachkenntnisse verfügen.

## Erläuterung zum Ersatzvermerk

Gemäß Vorwort zur EN wird das späteste Datum, zu dem nationale Normen, die der vorliegenden Norm entgegenstehen, zurückgezogen werden müssen, mit dow (date of withdrawal) festgelegt. Bis zum Zurückziehungsdatum (dow) 2018-04-30 ist somit die Anwendung folgender Norm(en) noch erlaubt:

ÖVE/ÖNORM EN 301 908-13 V7.1.1:2016-03-01.



**IMT cellular networks;  
Harmonised Standard covering the essential requirements  
of article 3.2 of the Directive 2014/53/EU;  
Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA)  
User Equipment (UE)**

Copyright © ETSI

---

Reference

REN/MSG-TFES-11-13-RED

---

Keywords3G, 3GPP, cellular, digital, E-UTRA, IMT, LTE,  
LTE-Advanced, mobile, radio, regulation, UMTS**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.  
All rights reserved.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction .....	8
1    Scope .....	9
2    References .....	11
2.1    Normative references .....	11
2.2    Informative references.....	11
3    Definitions, symbols and abbreviations .....	12
3.1    Definitions.....	12
3.2    Symbols .....	15
3.3    Abbreviations .....	16
4    Technical requirements specifications .....	18
4.1    Environmental profile.....	18
4.2    Conformance requirements .....	18
4.2.0    General.....	18
4.2.1    Introduction.....	18
4.2.2    Transmitter Maximum Output Power .....	19
4.2.2.1    Transmitter maximum output power for Single Carrier.....	19
4.2.2.1.1    Definition.....	19
4.2.2.1.2    Limits .....	19
4.2.2.1.3    Conformance .....	19
4.2.2.2    Transmitter output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	19
4.2.2.2.1    Definition.....	19
4.2.2.2.2    Limits .....	20
4.2.2.2.3    Conformance .....	20
4.2.2.3    Transmitter output power for UL-MIMO .....	20
4.2.2.3.1    Definition.....	20
4.2.2.3.2    Limits .....	21
4.2.2.3.3    Conformance .....	21
4.2.3    Transmitter Spectrum Emission Mask .....	21
4.2.3.1    Transmitter spectrum emission mask for Single Carrier.....	21
4.2.3.1.1    Definition.....	21
4.2.3.1.2    Limits .....	21
4.2.3.1.3    Conformance .....	23
4.2.3.2    Transmitter spectrum emission mask for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	23
4.2.3.2.1    Definition.....	23
4.2.3.2.2    Limits .....	23
4.2.3.2.3    Conformance .....	24
4.2.3.3    Transmitter spectrum emission mask for UL-MIMO .....	24
4.2.3.3.1    Definition.....	24
4.2.3.3.2    Limits .....	24
4.2.3.3.3    Conformance .....	24
4.2.3.4    Transmitter spectrum emission mask for Multi-Cluster PUSCH within a component carrier .....	24
4.2.3.4.1    Definition.....	24
4.2.3.4.2    Limits .....	25
4.2.3.4.3    Conformance .....	25
4.2.4    Transmitter Spurious Emissions .....	25
4.2.4.1    Transmitter spurious emissions for Single Carrier.....	25
4.2.4.1.1    Definition.....	25
4.2.4.1.2    Limits .....	25
4.2.4.1.3    Conformance .....	28

4.2.4.2	Transmitter spurious emissions for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	28
4.2.4.2.1	Definition.....	28
4.2.4.2.2	Limits .....	28
4.2.4.2.3	Conformance .....	30
4.2.4.3	Transmitter spurious emissions for UL-MIMO .....	31
4.2.4.3.1	Definition.....	31
4.2.4.3.2	Limits .....	31
4.2.4.3.3	Conformance .....	31
4.2.4.4	Transmitter spurious emissions for Multi-Cluster PUSCH within a component carrier.....	31
4.2.4.4.1	Definition.....	31
4.2.4.4.2	Limits .....	31
4.2.4.4.3	Conformance .....	31
4.2.5	Transmitter Minimum Output Power.....	31
4.2.5.1	Transmitter minimum output power for Single Carrier.....	31
4.2.5.1.1	Definition.....	31
4.2.5.1.2	Limits .....	32
4.2.5.1.3	Conformance .....	32
4.2.5.2	Transmitter minimum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA) .....	32
4.2.5.2.1	Definition.....	32
4.2.5.2.2	Limits .....	32
4.2.5.2.3	Conformance .....	32
4.2.5.3	Transmitter minimum output power for UL-MIMO .....	32
4.2.5.3.1	Definition.....	32
4.2.5.3.2	Limits .....	33
4.2.5.3.3	Conformance .....	33
4.2.6	Receiver Adjacent Channel Selectivity (ACS).....	33
4.2.6.1	Receiver Adjacent Channel Selectivity (ACS) for Single Carrier .....	33
4.2.6.1.1	Definition.....	33
4.2.6.1.2	Limits .....	33
4.2.6.1.3	Conformance .....	34
4.2.6.2	Receiver Adjacent Channel Selectivity (ACS) for Carrier Aggregation in DL-only bands .....	34
4.2.6.2.1	Definition.....	34
4.2.6.2.2	Limits .....	34
4.2.6.2.3	Conformance .....	34
4.2.7	Receiver Blocking Characteristics.....	35
4.2.7.1	Receiver Blocking Characteristics for Single Carrier .....	35
4.2.7.1.1	Definition.....	35
4.2.7.1.2	Limits .....	35
4.2.7.1.3	Conformance .....	36
4.2.7.2	Receiver Blocking Characteristics for Carrier Aggregation in DL-only bands.....	37
4.2.7.2.1	Definition.....	37
4.2.7.2.2	Limits .....	37
4.2.7.2.3	Conformance .....	38
4.2.8	Receiver Spurious Response.....	38
4.2.8.1	Receiver Spurious Response for Single Carrier .....	38
4.2.8.1.1	Definition.....	38
4.2.8.1.2	Limits .....	38
4.2.8.1.3	Conformance .....	39
4.2.8.2	Receiver Spurious Response for Carrier Aggregation in DL-only bands .....	39
4.2.8.2.1	Definition.....	39
4.2.8.2.2	Limits .....	39
4.2.8.2.3	Conformance .....	39
4.2.9	Receiver Intermodulation Characteristics.....	39
4.2.9.1	Receiver Intermodulation Characteristics for Single Carrier .....	39
4.2.9.1.1	Definition.....	39
4.2.9.1.2	Limits .....	39
4.2.9.1.3	Conformance .....	40
4.2.9.2	Receiver Intermodulation Characteristics for Carrier Aggregation in DL-only bands.....	40
4.2.9.2.1	Definition.....	40
4.2.9.2.2	Limits .....	40

4.2.9.2.3	Conformance .....	40
4.2.10	Receiver Spurious Emissions.....	40
4.2.10.1	Receiver Spurious Emissions for Single Carrier .....	40
4.2.10.1.1	Definition.....	40
4.2.10.1.2	Limits .....	41
4.2.10.1.3	Conformance .....	41
4.2.10.2	Receiver Spurious Emissions in DL-only bands .....	41
4.2.10.2.1	Definition.....	41
4.2.10.2.2	Limits .....	41
4.2.10.2.3	Conformance .....	41
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio.....	41
4.2.11.1	Transmitter adjacent channel leakage power ratio for Single Carrier .....	41
4.2.11.1.1	Definition.....	41
4.2.11.1.2	Limits .....	42
4.2.11.1.3	Conformance .....	42
4.2.11.2	Transmitter adjacent channel leakage power ratio for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	43
4.2.11.2.1	Definition.....	43
4.2.11.2.2	Limits .....	43
4.2.11.2.3	Conformance .....	44
4.2.11.3	Transmitter adjacent channel leakage power ratio for UL-MIMO .....	44
4.2.11.3.1	Definition.....	44
4.2.11.3.2	Limits .....	44
4.2.11.3.3	Conformance .....	45
4.2.11.4	Transmitter adjacent channel leakage power ratio for Multi-Cluster PUSCH within a component carrier .....	45
4.2.11.4.1	Definition.....	45
4.2.11.4.2	Limits .....	45
4.2.11.4.3	Conformance .....	45
4.2.12	Receiver Reference Sensitivity Level .....	46
4.2.12.0	General .....	46
4.2.12.1	Receiver Reference Sensitivity Level for Single Carrier .....	46
4.2.12.1.1	Definition.....	46
4.2.12.1.2	Limits .....	46
4.2.12.1.3	Conformance .....	46
5	Testing for compliance with technical requirements.....	47
5.1	Environmental conditions for testing .....	47
5.2	Interpretation of the measurement results .....	47
5.3	Essential radio test suites.....	48
5.3.0	General.....	48
5.3.1	Transmitter Maximum Output Power .....	48
5.3.1.1	Transmitter maximum output power for Single Carrier .....	48
5.3.1.1.1	Method of test.....	48
5.3.1.1.2	Test requirements .....	49
5.3.1.2	Transmitter maximum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA) .....	49
5.3.1.2.1	Method of test.....	49
5.3.1.2.2	Test requirements .....	50
5.3.1.3	Transmitter maximum output power for UL-MIMO .....	50
5.3.1.3.1	Method of test.....	50
5.3.1.3.2	Test requirements .....	50
5.3.2	Transmitter Spectrum Emission Mask .....	51
5.3.2.1	Transmitter spectrum emission mask for Single Carrier .....	51
5.3.2.1.1	Method of test.....	51
5.3.2.1.2	Test requirements .....	51
5.3.2.2	Transmitter spectrum emission mask for intra-band contiguous Carrier Aggregation (DL CA and UL CA) .....	52
5.3.2.2.1	Method of test.....	52
5.3.2.2.2	Test requirements .....	52
5.3.2.3	Transmitter spectrum emission mask for UL-MIMO .....	53
5.3.2.3.1	Method of test.....	53

5.3.2.3.2	Test requirements .....	53
5.3.2.4	Transmitter spectrum emission mask for Multi-Cluster PUSCH within a component carrier .....	53
5.3.2.4.1	Method of test.....	53
5.3.2.4.2	Test requirements .....	54
5.3.3	Transmitter Spurious Emissions .....	54
5.3.3.1	Transmitter spurious emissions for Single Carrier.....	54
5.3.3.1.1	Method of test.....	54
5.3.3.1.2	Test requirements .....	55
5.3.3.2	Transmitter spurious emissions for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	55
5.3.3.2.1	Method of test.....	55
5.3.3.2.2	Test requirements .....	56
5.3.3.3	Transmitter spurious emissions for UL-MIMO .....	56
5.3.3.3.1	Method of test.....	56
5.3.3.3.2	Test requirements .....	57
5.3.3.4	Transmitter spurious emissions for Multi-Cluster PUSCH within a component carrier .....	57
5.3.3.4.1	Method of test.....	57
5.3.3.4.2	Test requirements .....	58
5.3.4	Transmitter Minimum Output Power.....	58
5.3.4.1	Transmitter minimum output power for Single Carrier.....	58
5.3.4.1.1	Method of test.....	58
5.3.4.1.2	Test requirements .....	59
5.3.4.2	Transmitter minimum output power for intra-band contiguous Carrier Aggregation (DL CA and UL CA) .....	59
5.3.4.2.1	Method of test.....	59
5.3.4.2.2	Test requirements .....	59
5.3.4.3	Transmitter minimum output power for UL-MIMO .....	60
5.3.4.3.1	Method of test.....	60
5.3.4.3.2	Test requirements .....	60
5.3.5	Receiver Adjacent Channel Selectivity (ACS) .....	60
5.3.5.1	Receiver Adjacent Channel Selectivity (ACS) for Single Carrier .....	60
5.3.5.1.1	Method of test.....	60
5.3.5.1.2	Test requirements .....	61
5.3.5.2	Receiver Adjacent Channel Selectivity (ACS) for Carrier Aggregation in DL-only bands .....	62
5.3.5.2.1	Method of test.....	62
5.3.5.2.2	Test requirements .....	63
5.3.6	Receiver Blocking Characteristics .....	63
5.3.6.1	Receiver Blocking Characteristics for Single Carrier .....	63
5.3.6.1.1	Method of test.....	63
5.3.6.1.2	Test requirements .....	65
5.3.6.2	Receiver Blocking Characteristics for Carrier Aggregation in DL-only bands .....	65
5.3.6.2.1	Method of test.....	65
5.3.6.2.2	Test requirements .....	67
5.3.7	Receiver Spurious Response .....	67
5.3.7.1	Receiver Spurious Response for Single Carrier .....	67
5.3.7.1.1	Method of test.....	67
5.3.7.1.2	Test requirements .....	68
5.3.7.2	Receiver Spurious Response for Carrier Aggregation in DL-only bands .....	68
5.3.7.2.1	Method of test.....	68
5.3.7.2.2	Test requirements .....	68
5.3.8	Receiver Intermodulation Characteristics .....	68
5.3.8.1	Receiver Intermodulation Characteristics for Single Carrier .....	68
5.3.8.1.1	Method of test.....	68
5.3.8.1.2	Test requirements .....	69
5.3.8.2	Receiver Intermodulation Characteristics for Carrier Aggregation in DL-only bands.....	69
5.3.8.2.1	Method of test.....	69
5.3.8.2.2	Test requirements .....	70
5.3.9	Receiver Spurious Emissions.....	70
5.3.9.1	Receiver Spurious Emissions for Single Carrier .....	70
5.3.9.1.1	Method of test.....	70
5.3.9.1.2	Test requirements .....	71
5.3.9.2	Receiver Spurious Emissions in DL-only bands .....	71

5.3.9.2.1	Method of test.....	71
5.3.9.2.2	Test requirements .....	72
5.3.10	Transmitter Adjacent Channel Leakage Power Ratio .....	72
5.3.10.1	Transmitter adjacent channel leakage power ratio for Single Carrier .....	72
5.3.10.1.1	Method of test.....	72
5.3.10.1.2	Test requirements .....	73
5.3.10.2	Transmitter adjacent channel leakage power ratio for intra-band contiguous Carrier Aggregation (DL CA and UL CA).....	73
5.3.10.2.1	Method of test.....	73
5.3.10.2.2	Test requirements .....	74
5.3.10.3	Transmitter adjacent channel leakage power ratio for UL-MIMO.....	74
5.3.10.3.1	Method of test.....	74
5.3.10.3.2	Test requirements .....	75
5.3.10.4	Transmitter adjacent channel leakage power ratio for Multi-Cluster PUSCH within a component carrier .....	75
5.3.10.4.1	Method of test.....	75
5.3.10.4.2	Test requirements .....	76
5.3.11	Receiver Reference Sensitivity Level .....	76
5.3.11.1	Receiver Reference Sensitivity Level for Single Carrier .....	76
5.3.11.1.1	Method of test.....	76
5.3.11.1.2	Test requirements .....	77
<b>Annex A (normative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>78</b>
<b>Annex B (normative):</b>	<b>Environmental profile .....</b>	<b>79</b>
B.1	General .....	79
B.1.1	Introduction .....	79
B.1.2	Temperature .....	79
B.1.3	Voltage .....	79
B.1.4	Test environment.....	80
<b>Annex C (informative):</b>	<b>Bibliography.....</b>	<b>81</b>
History .....	82	

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.9] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 13 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.12].

National transposition dates	
Date of adoption of this EN:	12 July 2016
Date of latest announcement of this EN (doa):	31 October 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2017
Date of withdrawal of any conflicting National Standard (dow):	30 April 2018

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are NOT allowed in ETSI deliverables except when used in direct citation.

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

# 1 Scope

The present document applies to the following radio equipment type:

- User Equipment for Evolved Universal Terrestrial Radio Access (E-UTRA).

This radio equipment type is capable of operating in all or any part of the frequency bands given in tables from 1-1 through 1-5.

**Table 1-1: E-UTRA UE operating bands**

E-UTRA Band	Direction of UE transmission	E-UTRA operating bands
1	Transmit	1 920 MHz to 1 980 MHz
	Receive	2 110 MHz to 2 170 MHz
3	Transmit	1 710 MHz to 1 785 MHz
	Receive	1 805 MHz to 1 880 MHz
7	Transmit	2 500 MHz to 2 570 MHz
	Receive	2 620 MHz to 2 690 MHz
8	Transmit	880 MHz to 915 MHz
	Receive	925 MHz to 960 MHz
20	Transmit	832 MHz to 862 MHz
	Receive	791 MHz to 821 MHz
22	Transmit	3 410 MHz to 3 490 MHz
	Receive	3 510 MHz to 3 590 MHz
28	Transmit	703 MHz to 748 MHz
	Receive	758 MHz to 803 MHz
32 (note)	Transmit	N/A
	Receive	1 452 MHz to 1 496 MHz
33	Transmit and Receive	1 900 MHz to 1 920 MHz
34	Transmit and Receive	2 010 MHz to 2 025 MHz
38	Transmit and Receive	2 570 MHz to 2 620 MHz
40	Transmit and Receive	2 300 MHz to 2 400 MHz
42	Transmit and Receive	3 400 MHz to 3 600 MHz
43	Transmit and Receive	3 600 MHz to 3 800 MHz

NOTE: Restricted to E-UTRA operation when carrier aggregation is configured. The downlink operating band is paired with the uplink operating band (external) of the carrier aggregation configuration that is supporting the configured Pcell.

**Table 1-2: E-UTRA UE Intra-band contiguous CA operating bands**

E-UTRA CA Band	E-UTRA Band	Direction of UE transmission	E-UTRA operating bands
CA_1	1	Transmit	1 920 MHz to 1 980 MHz
		Receive	2 110 MHz to 2 170 MHz
CA_3	3	Transmit	1 710 MHz to 1 785 MHz
		Receive	1 805 MHz to 1 880 MHz
CA_7	7	Transmit	2 500 MHz to 2 570 MHz
		Receive	2 620 MHz to 2 690 MHz
CA_38	38	Transmit and Receive	2 570 MHz to 2 620 MHz
CA_40	40	Transmit and Receive	2 300 MHz to 2 400 MHz
CA_42	42	Transmit and Receive	3 400 MHz to 3 600 MHz