




Edition 2.0 2010-12

INTERNATIONAL STANDARD



Protection against lightning –
Part 3: Physical damage to structures and life hazard





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Email: inmail@iec.ch Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub
- The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: www.iec.ch/online_news/justpub
Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Centre: www.iec.ch/web

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 2.0 2010-12

INTERNATIONAL STANDARD



Protection against lightning –
Part 3: Physical damage to structures and life hazard



ICS 29.020; 91.120.40 ISBN 978-2-88912-282-0

CONTENTS

FO	REW	ORD		7	
IN	TROD	UCTION	N	10	
1	Scop	oe		11	
2	Norn	native re	eferences	11	
3	Term	ns and d	definitions	12	
4	Liah	tnina pr	otection system (LPS)	15	
•	4.1	Class	of LPS	15	
	4.2		n of the LPS		
	4.3	•	nuity of steelwork in reinforced concrete structures		
5			ntning protection system		
	5.1	General			
		5.1.1			
		5.1.2			
		5.1.3	Use of natural components		
	5.2	Air-ter	mination systems	18	
		5.2.1	General		
		5.2.2	Positioning	18	
		5.2.3	Air-terminations against flashes to the side of tall structures		
		5.2.4	Construction		
		5.2.5	Natural components		
	5.3		-conductor systems		
		5.3.1	General	21	
		5.3.2	Positioning for an isolated LPS		
		5.3.3	Positioning for a non-isolated LPS		
		5.3.4	Construction		
		5.3.5	Natural components Test joints		
	5.4	5.3.6	termination system		
	5.4	5.4.1	General		
		5.4.2	Earthing arrangement in general conditions		
		5.4.3	Installation of earth electrodes		
		5.4.4	Natural earth electrodes		
	5.5		onents		
		5.5.1	General		
		5.5.2	Fixing	28	
		5.5.3	Connections	28	
	5.6	Materials and dimensions		29	
		5.6.1	Materials	29	
		5.6.2	Dimensions	29	
6	Inter	nal ligh	tning protection system	31	
	6.1	Gener	al	31	
	6.2	-	ing equipotential bonding		
		6.2.1	General		
		6.2.2	Lightning equipotential bonding for metal installations		
		6.2.3	Lightning equipotential bonding for external conductive parts		
		6.2.4	Lightning equipotential bonding for internal systems	34	

		6.2.5	be protected	2/
	6.3	Flectric	cal insulation of the external LPS	
	0.0	6.3.1	General	
		6.3.2	Simplified approach	
		6.3.3	Detailed approach	
7	Main	tenance	and inspection of an LPS	37
	7.1	Genera	al	37
	7.2		ation of inspections	
	7.3	Order o	of inspections	37
	7.4	Mainte	nance	37
8	Prote		easures against injury to living beings due to touch and step voltages	
	8.1		ion measures against touch voltages	
	8.2		ion measures against step voltages	
Anr	nex A	(normat	ive) Positioning the air-termination system	39
			ive) Minimum cross-section of the entering cable screen in order to sparking	45
Anr	nex C	(informa	ative) Evaluation of the separation distance s	46
			ive) Additional information for LPS in the case of structures with a	52
Anr insp	nex E pectio	(informa n of ligh	ative) Guidelines for the design, construction, maintenance and tning protection systems	59
		,		
Fig	ure 1	– Protec	ction angle corresponding to the class of LPS	19
			n a down-conductor	
_		-	um length I_1 of each earth electrode according to the class of LPS	
_			ime protected by a vertical air-termination rod	
_			Ime protected by a vertical air-termination rod	
•			ime protected by a wire air-termination system	
_			ime protected by a wife an-termination system	+0
			method and rolling sphere method	41
			ime protected by non-isolated wires combined in a mesh according to I and the protection angle method	42
Fig	ure A.	6 – Des	ign of an air-termination system according to the rolling sphere	
		•	ues of coefficient $k_{\rm c}$ in the case of a wire air-termination system	
_			ues of coefficient k_c in the case of multiple down-conductors system	
			ues of coefficient k_c in the case of multiple down-conductors system	71
				49
Fig	ure C.	4 – Exa	mples of calculation of the separation distance in the case of multiple with an interconnecting ring of the down-conductors at each level	
			ues of coefficient $k_{\rm C}$ in the case of a meshed air-termination system,	00
			own-conductors system	51
		•	design flow diagram	
_			design for a cantilevered part of a structure	
_			suring the overall electrical resistance	68

Figure E.4 – Equipotential bonding in a structure with a steel reinforcement	70
Figure E.5 – Typical methods of joining reinforcing rods in concrete (where permitted)	71
Figure E.6 – Example of clamps used as joints between reinforcing rods and conductors	72
Figure E.7 – Examples for connection points to the reinforcement in a reinforced concrete wall.	73
Figure E.8 – Use of metallic facade as natural down-conductor system and connection of facade supports	77
Figure E.9 – Connection of the continuous strip windows to a metal facade covering	
Figure E.10 – Internal down-conductors in industrial structures	81
Figure E.11 – Installation of bonding conductors in reinforced concrete structures and flexible bonds between two reinforced concrete parts	83
Figure E.12 – Protection angle method air-termination design for different heights according to Table 2	87
Figure E.13 – Isolated external LPS using two isolated air-termination masts designed according to the protection angle air-termination design method	88
Figure E.14 – Isolated external LPS using two isolated air-termination masts, interconnected by horizontal catenary wire	89
Figure E.15 – Example of design of an air-termination of a non-isolated LPS by air-termination rods	90
Figure E.16 – Example of design of an air-termination of a non isolated LPS by a horizontal wire according to the protection angle air-termination design method	91
Figure E.17 – Protected volume of an air- termination rod on a sloped surface using the protection angle design method	92
Figure E.18 – Design of an LPS air-termination conductor network on a structure with complicated shape	93
Figure E.19 – Design of an LPS air-termination according to the protection angle method, mesh method and general arrangement of air-termination elements	94
Figure E.20 – Space protected by two parallel air-termination horizontal wires or two air-termination rods ($r > h_t$)	95
Figure E.21 – Three examples of design of non-isolated LPS air-termination according to the mesh method air-termination design	98
Figure E.22 – Four examples of details of an LPS on a structure with sloped tiled roofs	100
Figure E.23 – Air-termination and visually concealed conductors for buildings less than 20 m high, with sloping roofs	101
Figure E.24 – Construction of an LPS using natural components on the roof of the structure	103
Figure E.25 – Positioning of the external LPS on a structure made of isolating material e.g. wood or bricks with a height up to 60 m with flat roof and with roof fixtures	104
Figure E.26 – Construction of air-termination network on a roof with conductive covering where puncturing of the covering is not acceptable	105
Figure E.27 – Construction of external LPS on a structure of steel-reinforced concrete using the reinforcement of the outer walls as natural components	106
Figure E.28 – Example of an air-termination stud used on car park roofs	107
Figure E.29 – Air-termination rod used for protection of a metallic roof fixture with electric power installations which are not bonded to the air-termination system	108
Figure E.30 – Method of achieving electrical continuity on metallic parapet capping	109
Figure E.31 – Metallic roof fixture protected against direct lightning interception, connected to air-termination system	112

Figure E.32 – Examplesof lightning protection of a house with a TV antenna	115
Figure E.33 – Installation of lightning protection of metallic equipment on a roof against a direct lightning flash	116
Figure E.34 – Connection of natural air-termination rod to air-termination conductor	118
Figure E.35 – Construction of the bridging between the segments of the metallic facade plates	119
Figure E.36 – Installation of external LPS on a structure of insulating material with different roof levels	122
Figure E.37 – Five examples of geometry of LPS conductors	123
Figure E.38 – Construction of an LPS using only two down-conductors and foundation earth electrodes	124
Figure E.39 – Four examples of connection of earth-termination to the LPS of structures using natural down-conductors (girders) and detail of a test joint	128
Figure E.40 – Construction of foundation earth ring for structures of different foundation design	132
Figure E.41 – Two examples of vertical electrodes in type A earthing arrangement	134
Figure E.42 – Meshed earth-termination system of a plant	137
Figure E.43 – Example of an equipotential bonding arrangement	144
Figure E.44 – Example of bonding arrangement in a structure with multiple point entries of external conductive parts using a ring electrode for interconnection of bonding bars	145
Figure E.45 – Example of bonding in the case of multiple point entries of external conductive parts and an electric power or communication line using an internal ring conductor for interconnection of the bonding bars	146
Figure E.46 – Example of bonding arrangement in a structure with multiple point entries of external conductive parts entering the structure above ground level	147
Figure E.47 – Directions for calculations of the separation distance, s, for a worst case lightning interception point at a distance / from the reference point according to 6.3	149
Table 1 – Relation between fightning protection levels (LPL) and class of LPS (see IEC 62305-1)	16
Table 2 – Maximum values of rolling sphere radius, mesh size and protection angle corresponding to the class of LPS	19
Table 3 – Minimum thickness of metal sheets or metal pipes in air-termination systems	21
Table 4 – Typical preferred values of the distance between down-conductors according to the class of LPS	22
Table 5 – LPS materials and conditions of use	28
Table 6 – Material, configuration and minimum cross-sectional area of air-termination conductors, air-termination rods, earth lead-in rods and down-conductors	30
Table 7 – Material, configuration and minimum dimensions of earth electrodes	31
Table 8 – Minimum dimensions of conductors connecting different bonding bars or connecting bonding bars to the earth-termination system	33
Table 9 – Minimum dimensions of conductors connecting internal metal installations to the bonding bar	33
Table 10 – Isolation of external LPS – Values of coefficient k_i	35
Table 11 – Isolation of external LPS – Values of coefficient $k_{ m m}$	35
Table 12 – Isolation of external LPS – Approximated values of coefficient $k_{\rm c}$	
Table B.1 – Cable length to be considered according to the condition of the screen	
Table F.1 – Suggested fixing centres.	99



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROTECTION AGAINST LIGHTNING -

Part 3: Physical damage to structures and life hazard

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62305-3 has been prepared by IEC technical committee 81: Lightning protection.

This second edition cancels and replaces the first edition, published in 2006, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- 1) Minimum thicknesses of metal sheets or metal pipes given in Table 3 for air-termination systems are assumed as not able to prevent hot-spot problems.
- 2) Steel with electro-deposited copper is introduced as material suitable for LPS.
- 3) Some cross-sectional areas of LPS conductors were slightly modified.
- 4) For bonding purposes, isolating spark gaps are used for metal installations and SPD for internal systems.

- 5) Two methods simplified and detailed are provided for evaluation of separation distance.
- 6) Protection measures against injuries of living beings due to electric shock are considered also inside the structure.
- 7) Improved information for LPS in the case of structures with a risk of explosion are given in Annex D (normative).

The text of this standard is based on the following documents:

FDIS	Report on voting	
81/372/FDIS	81/382/RVD	

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted, as closely as possible, in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62305 series, under the general title *Protection against lightning*, can be found on the IEC website.